

Modern Beamer Presentations with the MTHEME package

Matthias Vogelgesang
matthias.vogelgesang@gmail.com

? from ?

1 Introduction

Beamer is an awesome way to make presentations with LaTeX. But the stock themes do not necessarily look particularly nice and the custom themes often scream “Beamer” at first sight. The goal of MTHEME is to provide a modern Beamer theme with minimal visual noise. It provides section slides with a neat progress bar and it is intended to be used with [Fira Sans](#), a gorgeous typeface commissioned by Mozilla and designed by [Carrois](#). Hence to get the best results you should have installed the Fira typeface and use XeTeX to typeset your slides. Nevertheless this is no hard dependency. The theme also works fine with pdfTeX and the Computer Modern typeface.

The codebase is maintained on [GitHub](#). So if you have issues, find mistakes in the manual or want to contribute – to make the theme even better – get in contact there.

2 Getting Started

To get started with the theme is very simple. The following code shows a minimal example of a Beamer presentation using the MTHEME.

```
\documentclass[10pt]{beamer}  
\usetheme{m} % load mtheme
```

```

\title{A modern beamer theme} % define title
\date{\today} % define date
\author{Matthias Vogelgesang} % define author
\institute{Institute} % define institute
\begin{document}
\maketitle % create titlepage
\section{First Section} % create section
\begin{frame}{First Frame} % first frame
    Lorem ipsum dolor sit amet, ...
\end{frame}
\begin{frame}{Second Frame} % second frame
    Lorem ipsum dolor sit amet, ...
\end{frame}
\end{document}

```

3 Known Issues

4 Changelog

5 License

The theme itself is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](#). This means that if you change the theme and re-distribute it, you must retain the copyright notice header and license it under the same CC-BY-SA license. This does not affect the presentation that you create with the theme.

6 Contributors

- [matze](#) Matthias Vogelgesang
- [rchurchley](#) Ross Churchley
- [benjamin-weiss](#) Benjamin Weiss
- [eddelbuettel](#) Dirk Eddelbuettel
- [ronnychevalier](#) Ronny Chevalier

- **jdahm** Johann Dahm
- **Schwefelsaeure**
- **awalterschulze** Walter Schulze
- **ehahn** Erik Hahn
- **ChipmunkMath**
- **timbers** Finbarr Timbers
- **kdungs** Kevin Dungs
- **Leonidas-from-XIV** Marek Kubica
- **Oip** Robin Buse
- **cuzcomd**

7 Implementation

7.1 Main Theme

Options

```

1
2 \newif\if@useTitleProgressBar
3 \useTitleProgressBarfalse
4 \DeclareOptionBeamer{usetitleprogressbar}{
5   \useTitleProgressBartrue
6 }

usetotalslideindicator

7
8 \newif\if@useTotalSlideIndicator
9 \useTotalSlideIndicatorfalse
10 \DeclareOptionBeamer{usetotalslideindicator}{
11   \useTotalSlideIndicatortrue
12 }

noslidenumbers

13
14 \newif\if@noSlideNumbers
15 \useNoSlideNumbersfalse
16 \DeclareOptionBeamer{noslidenumbers}{
17   \useNoSlideNumberstrue
18 }
```

```

nosectionsslide
19
20 \newif\if@noSectionSlide
21 \if@noSectionSlidefalse
22 \DeclareOptionBeamer{nosectionslide}{
23   \if@noSectionSlidetrue
24 }

protectframetitle
25
26 \newif\if@protectFrameTitle
27 \if@protectFrameTitlefalse
28 \DeclareOptionBeamer{protectframetitle}{
29   \if@protectFrameTitltrue
30 }

nooffset
31
32 \newlength{\@mtheme@voffset}
33 \setlength{\@mtheme@voffset}{2em}
34 \DeclareOptionBeamer{noffset}{

35   \setlength{\@mtheme@voffset}{0em}
36 }

blockbg
37
38 \DeclareOptionBeamer{blockbg}{

39   \PassOptionsToPackage{blockbg}{beamercolorthememetropolis}%
40 }

Unknown option error handling
41
42 \DeclareOptionBeamer*{
43   \PackageWarning{beamerthemem}{Unknown option `\\CurrentOption'}`}
44 }
45 \ProcessOptionsBeamer

mthemetitleformat

\mthemetitleformat
46
47 \def\mthemetitleformat#1{\scshape #1}

```

```

48
49 \mode

```

Set beamer title page template

```
77
78 \setbeamertemplate{title page}
79 {
80   \begin{minipage}[b][\paperheight]{\textwidth}
81     \vspace*{\@mtheme@voffset}
82
83     \ifx\inserttitlegraphic\empty\else
84       \% \inserttitlegraphic is nonempty
85       \vbox to 0pt
86         \% display title graphic without changing the position of other el-
87         ements
88         \vspace*{2em}
89         \usebeamercolor[fg]{titlegraphic}%
90         \inserttitlegraphic%
91         }%
92         \nointerlineskip%
93     }
94     \fi
95   \vfill%
96
97   \ifx\inserttitle\empty\else
98     \% \inserttitle is nonempty
99     \raggedright%
100    \linespread{1.0}%
101    \usebeamertfont{title}%
102    \usebeamercolor[fg]{title}%
103    \mthemetitleformat{\inserttitle}%
104    \vspace*{0.5em}
105  }%
106  \fi
107
108  \ifx\insertsubtitle\empty\else
109    \% \insertsubtitle is nonempty
110    \usebeamertfont{subtitle}%
111    \usebeamercolor[fg]{subtitle}%
112    \insertsubtitle%
113    \vspace*{0.5em}%
114  }%
```

```

115 \fi
116
117 \begin{tikzpicture}
118   \usebeamercolor{title separator}
119   \draw[fg] (0, 0) -- (\textwidth, 0);
120 \end{tikzpicture}%
121 \vspace*{1em}%
122
123 \ifx\beamer@shortauthor\empty\else
124   {{% \insertauthor is always nonempty by beamer's definition, so we must
125     % test another macro which is initialized by \author{...}
126     % For details, see http://tex.stackexchange.com/questions/241306/
127     \usebeamertfont{author}%
128     \usebeamercolor[fg]{author}%
129     \insertauthor%
130     \par%
131     \vspace*{0.25em}%
132   }%
133 \fi
134
135 \ifx\insertdate\empty\else
136   {{% \insertdate is nonempty
137     \usebeamertfont{date}%
138     \usebeamercolor[fg]{date}%
139     \insertdate%
140     \par%
141   }%
142 \fi
143
144 \ifx\insertinstitute\empty\else
145   {{% \insertinstitute is nonempty
146     \vspace*{3mm}%
147     \usebeamertfont{institute}%
148     \usebeamercolor[fg]{institute}%
149     \insertinstitute%
150     \par%
151   }%
152 \fi
153
154 \vfill

```

```

155      \vspace*{\themevoffset}
156  \end{minipage}
157 }

    Progressbar

158
159 \RequirePackage{calc}

\inserttotalframenumber

160
161 \def\inserttotalframenumber{100} % prevent \progressbar@percent from get-
    ting too big on first compile

162
163 \newlength{\progressbar@percent}

\progressbar

164
165 \newcommand{\progressbar}[1]{%
166   \setlength{\progressbar@percent}{%
167     #1 * \ratio{\insertframenumber pt}{\inserttotalframenumber pt}%
168   }%
169   \begin{tikzpicture}[tight background]
170     \usebeamercolor{progress bar}
171     \draw[bg, fill=bg] (0,0) rectangle (#1, 0.4pt);
172     \draw[fg, fill=fg] (0,0) rectangle (\progressbar@percent, 0.4pt);
173   \end{tikzpicture}%
174 }

    Commands

\insertsectionHEAD

175
176 \newcommand{\insertsectionHEAD}{%
177   \expandafter\insertsectionHEADaux\insertsectionhead}

\insertsectionHEADaux

178
179 \newcommand{\insertsectionHEADaux}[3]{\themetitleformat{#3}}%

    Create a plain frame with dark background

```

```

\plain
180
181 \newcommand{\plain}[2][]{
182   \begingroup
183     \setbeamercolor{background canvas}{use=palette primary, parent=palette pri-
184     \begin{frame}{#1}
185       \centering
186       \vfill
187       \vspace{1em}
188       \usebeamercolor[fg]{palette primary}
189       \usebeamertfont{section title}
190       \mthemetitleformat{#2}
191       \vfill
192     \end{frame}
193   \endgroup
194 }

Itemize tweaks
195
196 \setlength{\leftmargini}{1em}
197 \setlength{\leftmarginii}{1em}
198 \setlength{\leftmarginiii}{1em}

\itemBullet
199
200 \newcommand{\itemBullet}{\cdot}

201
202 \setbeamertemplate{itemize item}{\itemBullet}
203 \setbeamertemplate{itemize subitem}{\itemBullet}
204 \setbeamertemplate{itemize subsubitem}{\itemBullet}
205 \setlength{\parskip}{0.5em}

Sections
206
207 \setbeamertemplate{section page}
208 {
209   \vspace{2em}
210   \centering

```

```

211 \begin{minipage}{22em}
212   \usebeamercolor[fg]{section title}
213   \usebeamertfont{section title}
214   \insertsectionHEAD\[-1ex]
215   \progressbar{\textwidth}
216 \end{minipage}
217 \par
218 }

Insert frame with section title at every section start

219
220 \if@noSectionSlide\else%
221   \AtBeginSection[]
222   {
223     \ifbeamer@inframe
224       \sectionpage
225     \else
226       \frame[plain]{\sectionpage}
227     \fi
228   }
229 \fi

Captions

230
231 \setbeamertemplate{caption label separator}{: }
232 \setbeamertemplate{caption}[numbered]

Footline/footnote

233
234 \usenavigationsymbolstemplate{}
235 \setbeamertemplate{footline}
236 {%
237 \begin{beamercolorbox}[wd=\textwidth,ht=3ex,dp=3ex,leftskip=0.3cm,rightskip=0.3cm]{}
238   \hfill\usebeamertfont{page number in head/foot}%
239 \if@noSlideNumbers%
240   %Purposefully left blank to display no slide number.%
241 \else%
242   \if@useTotalSlideIndicator%
243     \insertframenumber/\inserttotalframenumber%
244   \else%
245     \insertframenumber%

```

```

246      \fi%
247  \fi%
248 \end{beamercolorbox}%
249 }
250 \setbeamertemplate{footnote}%
251 {%
252   \parindent 0em\noindent%
253   \raggedright
254   \usebeamercolor{footnote}\hbox to 0.8em{\hfil\insertfootnotemark}\insertfootnotetext{%
255 }

Frametitle

256
257 \setbeamertemplate{frametitle}{%
258 \nointerlineskip
259 \begin{beamercolorbox}[wd=\paperwidth, leftskip=0.3cm, rightskip=0.3cm, ht=2.5ex, dp=1.5ex]{frametitle}%
260 \usebeamertfont{frametitle}%
261 \if@protectFrameTitle%
262   \mthemetitleformat{\protect\insertframetitle}%
263 \else%
264   \mthemetitleformat{\insertframetitle}%
265 \fi%
266 \end{beamercolorbox}%
267 \if@useTitleProgressBar
268   \nointerlineskip
269   \begin{beamercolorbox}[wd=\paperwidth, ht=0.4pt, dp=0pt]{frametitle}%
270     \progressbar{\paperwidth}%
271   \end{beamercolorbox}%
272 \fi
273 \vspace{\@mtheme@voffset}%
274 }

pgfplots
Colors
TolColors from http://www.r-bloggers.com/the-paul-tol-21-color-salute/

275
276 \definecolor{TolColor1}{HTML}{332288}    % dark purple
277 \definecolor{TolColor2}{HTML}{6699CC}    % dark blue
278 \definecolor{TolColor3}{HTML}{88CCEE}    % light blue
279 \definecolor{TolColor4}{HTML}{44AA99}    % light green

```

```

280 \definecolor{TolColor5}{HTML}{117733}      % dark green
281 \definecolor{TolColor6}{HTML}{999933}      % dark brown
282 \definecolor{TolColor7}{HTML}{DDCC77}      % light brown
283 \definecolor{TolColor8}{HTML}{661100}      % dark red
284 \definecolor{TolColor9}{HTML}{CC6677}      % light red
285 \definecolor{TolColor10}{HTML}{AA4466}      % light pink
286 \definecolor{TolColor11}{HTML}{882255}      % dark pink
287 \definecolor{TolColor12}{HTML}{AA4499}      % light purple

    Color cycles

288
289 \pgfplotscreateplotcyclelist{mbarplot cycle}{%
290   {draw=TolColor2, fill=TolColor2!70},
291   {draw=TolColor7, fill=TolColor7!70},
292   {draw=TolColor4, fill=TolColor4!70},
293   {draw=TolColor11, fill=TolColor11!70},
294   {draw=TolColor1, fill=TolColor1!70},
295   {draw=TolColor8, fill=TolColor8!70},
296   {draw=TolColor6, fill=TolColor6!70},
297   {draw=TolColor9, fill=TolColor9!70},
298   {draw=TolColor10, fill=TolColor10!70},
299   {draw=TolColor12, fill=TolColor12!70},
300   {draw=TolColor3, fill=TolColor3!70},
301   {draw=TolColor5, fill=TolColor5!70},
302 }
303 \pgfplotscreateplotcyclelist{mlineplot cycle}{%
304   {TolColor2, mark=*, mark size=1.5pt},
305   {TolColor7, mark=square*, mark size=1.3pt},
306   {TolColor4, mark=triangle*, mark size=1.5pt},
307   {TolColor6, mark=diamond*, mark size=1.5pt},
308 }

    Styles

309
310 \pgfplotsset{
311   compat=1.9,
312   mbaseplot/.style={
313     legend style={
314       draw=none,
315       fill=none,
316       cells={anchor=west},

```

```

317   },
318   x tick label style={
319     font=\footnotesize
320   },
321   y tick label style={
322     font=\footnotesize
323   },
324   legend style={
325     font=\footnotesize
326   },
327   major grid style={
328     dotted,
329   },
330   axis x line*=bottom,
331 },
332 mlineplot/.style={
333   mbaseplot,
334   xmajorgrids=true,
335   ymajorgrids=true,
336   major grid style={dotted},
337   axis x line=bottom,
338   axis y line=left,
339   legend style={
340     cells={anchor=west},
341     draw=none
342   },
343   cycle list name=mlineplot cycle,
344 },
345 mbarplot base/.style={
346   mbaseplot,
347   bar width=6pt,
348   axis y line*=none,
349 },
350 mbarplot/.style={
351   mbarplot base,
352   ybar,
353   xmajorgrids=false,
354   ymajorgrids=true,
355   area legend,
356   legend image code/.code=%

```

```

357      \draw[#1] (0cm,-0.1cm) rectangle (0.15cm,0.1cm);
358  },
359  cycle list name=mbarplot cycle,
360 },
361 horizontal mbarplot/.style={
362   mbarplot base,
363   xmajorgrids=true,
364   ymajorgrids=false,
365   xbar stacked,
366   area legend,
367   legend image code/.code={%
368     \draw[#1] (0cm,-0.1cm) rectangle (0.15cm,0.1cm);
369   },
370   cycle list name=mbarplot cycle,
371 },
372 disable thousands separator/.style={
373   /pgf/number format/.cd,
374   1000 sep={}
375 },
376 }

377
378 \mode<all>
      misc

379
380 \let\otp\titlepage

\ttitlepage
381
382 \renewcommand{\titlepage}{\otp\addtocounter{framenumber}{-1}}


\mreducelistspacing
383
384 \newcommand{\mreducelistspacing}{\vspace{-\topsep}}
385
386 \linespread{1.15}

```

7.2 Font Theme

Font Definitions

```
387
388 \RequirePackage[no-math]{fontspec}
389 \defaultfontfeatures{Mapping=tex-text}
390 \setsansfont[BoldItalicFont={Fira Sans Italic},%
391           ItalicFont={Fira Sans Light Italic},%
392           BoldFont={Fira Sans}]{Fira Sans Light}
393 \setmonofont{Fira Mono}
394 \newfontfamily\ExtraLight{Fira Sans ExtraLight}
395 \newfontfamily\Light{Fira Sans Light}
396 \newfontfamily\Book{Fira Sans}
397 \newfontfamily\Medium{Fira Sans Medium}
398 \AtBeginEnvironment{tabular}{%
399   \setsansfont[BoldFont={Fira Sans},%
400             Numbers={Monospaced}]{Fira Sans Light}%
401 }
```

Font Assignment

```
402
403 \setbeamerfont{title}{family=\Book, size=\Large}
404 \setbeamerfont{author}{family=\ExtraLight, size=\small}
405 \setbeamerfont{date}{family=\ExtraLight, size=\small}
406 \setbeamerfont{section title}{family=\Book, size=\Large}
407 \setbeamerfont{block title}{family=\Book, size=\normalsize}
408 \setbeamerfont{block title alerted}{family=\Book, size=\normalsize}
409 \setbeamerfont{subtitle}{family=\Light, size=\fontsize{12}{14}}
410 \setbeamerfont{frametitle}{family=\Book, size=\large}
411 \setbeamerfont{caption}{size=\small}
412 \setbeamerfont{caption name}{family=\Book}
413 \setbeamerfont{description item}{family=\Book}
414 \setbeamerfont{page number in head/foot}{size=\scriptsize}
```

Bibliography

```
415
416 \setbeamerfont{bibliography entry author}{family=\Light, size=\normalsize}
417 \setbeamerfont{bibliography entry title}{family=\Book, size=\normalsize}
418 \setbeamerfont{bibliography entry location}{family=\Light, size=\normalsize}
419 \setbeamerfont{bibliography entry note}{family=\Light, size=\small}
420 \linespread{1.15}
```

7.3 Color Theme

Options

```
421  
422 \newif\if@beamer@metropolis@blockbg  
423 \if@beamer@metropolis@blockbgfalse  
424 \DeclareOptionBeamer{blockbg}{  
425     \if@beamer@metropolis@blockbgtrue  
426 }
```

Unknown option error handling

```
427  
428 \DeclareOptionBeamer*{  
429   \PackageWarning{beamercolorthememetropolis}{Unknown option `\\CurrentOption'}%  
430 }  
431 \ProcessOptionsBeamer
```

Colors

```
432  
433 \definecolor{mDarkBrown}{HTML}{604c38}  
434 \definecolor{mDarkTeal}{HTML}{23373b}  
435 \definecolor{mLightBrown}{HTML}{EB811B}  
436 \definecolor{mLightGreen}{HTML}{14B03D}
```

Base Colors

```
437  
438 \setbeamercolor{normal text}{  
439   fg=mDarkTeal,  
440   bg=black!2  
441 }  
442 \setbeamercolor{alerted text}{  
443   fg=mLightBrown  
444 }  
445 \setbeamercolor{example text}{  
446   fg=mLightGreen  
447 }
```

Derived Colors

```
448  
449 \setbeamercolor{titlelike}{use=normal text, parent=normal text}  
450 \setbeamercolor{structure}{%
```

```

451   fg=normal text.fg
452 }

Frame titles and plain slides

453
454 \setbeamercolor{frametitle}{use=palette primary, parent=palette pri-
    mary}

```

The “primary” palette should be used for the most important navigational elements, and possibly of other elements. The metropolis color theme uses it for frame titles and slides.

```

455
456 \setbeamercolor{palette primary}{%
457   use=normal text,
458   fg=normal text.bg,
459   bg=normal text.fg
460 }

```

Progress bar and title separator

```

461
462 \setbeamercolor{title separator}{use=progress bar, parent=progress bar}
463 \setbeamercolor{progress bar}{%
464   use=alerted text,
465   fg=alerted text.fg,
466   bg=normal text.bg!50!fg
467 }

```

Blocks

```

468
469 \if@beamer@metropolis@blockbg
470   \setbeamercolor{block title}{%
471     use=normal text,
472     fg=normal text.fg,
473     bg=normal text.bg!80!fg
474   }
475 \else
476   \setbeamercolor{block title}{use=normal text, parent=normal text}
477 \fi
478 \setbeamercolor{block title alerted}{%
479   use={block title, alerted text},
480   bg=block title.bg,

```

```
481     fg=alerted text.fg
482 }
483 \setbeamercolor{block title example}{%
484     use={block title, example text},
485     bg=block title.bg,
486     fg=example text.fg
487 }
488 \setbeamercolor{block body alerted}{use=block body, parent=block body}
489 \setbeamercolor{block body example}{use=block body, parent=block body}
490 \setbeamercolor{block body}{%
491     use={block title, normal text},
492     bg=block title.bg!50!normal text.bg
493 }
```

Footnotes

```
494
495 \setbeamercolor{footnote}{fg=normal text.fg!90}
496 \setbeamercolor{footnote mark}{fg=.}
497 \mode<all>
```